



WHEN USING
ACTIVE TRIM
USE GUIDE NO.
10-997

1/4" FINISH WASHER
2 PLACES
1/4-20 x 2-1/8 FHMS
2 PLACES

MTG. HOLES 1295 PANIC
AND 9500LV TRIM
SEE DWG. 10-936 FOR
COMPLETE INSTALLATION
OF 1295 PANIC

1295 PANIC

LOCATION OF ϕ
PER DWG. 10-936

#17/64 ϕ THRU
4 PLACES

17/64 ϕ THRU

1-1/2 REF.

6-5/16

39-1/4" FROM BTM
OF DOOR

PANIC SIDE (INSIDE)
ACTIVE STILE

TRIM SIDE (OUTSIDE)
ACTIVE STILE

9500LVDT-01 OUTSIDE TRIM (SHOWN)

WITH ROUND LEVER

DIMENSIONAL TOLERANCES UNLESS OTHERWISE SPECIFIED		APPROVALS	DATE
DECIMAL DIMENSIONS .XX	$\pm .010$	APPROVED	
DECIMAL DIMENSIONS .XXX	$\pm .005$	CHECKED	
ANGULAR \pm	$\frac{\circ}{16}$ FRACTIONAL $\pm 1/64$	DRAWN	R.M. 03/05/01
MATERIAL		SCALE	NONE

Jackson
CORPORATION

3447 UNION PACIFIC AVE.
LOS ANGELES, CALIF. 90023

NEXT ASSY.	FINISH
QTY. USED	HEAT TREAT

9500LV-01/02 SER. INST.
GUIDE

SHEET 1 OF 1 SHEETS	
DWG. NO.	REV.
10-1015	B