


COMPANY NAME \_\_\_\_\_ PHONE \_\_\_\_\_  
CONTACT \_\_\_\_\_ ACCOUNT NO. \_\_\_\_\_ FAX \_\_\_\_\_  
JOB NAME \_\_\_\_\_ EMAIL \_\_\_\_\_

QUOTE     ORDER P.O. # \_\_\_\_\_    DATE \_\_\_\_\_



Use the Door Swing Chart to determine how the door(s) should be handed.

SERIES	STANDARD PROFILE DIMENSIONS			
	THICKNESS	STILE	TOP RAIL	BOTTOM RAIL
400T MEDIUM STILE THERMAL DOOR	1-3/4"	4-1/4"	4-5/16"	7-1/4"
400AT MEDIUM STILE ADVANCE THERMAL DOOR	1-3/4"	4-1/4" (Foam Filled)	4-5/16" (Foam Filled)	7-1/4" (Foam Filled)
OPTIONAL				10"

**APPLICATION : MODERATE TO HEAVY TRAFFIC**

**DOOR STILE                      APPLICATION**

400T Medium Stile Thermal Door

400AT Medium Stile Advance Thermal Door

**DOOR FINISH**

11 - Clear Anodized Class I - Standard

22 - Dark Bronze / Black Anodized Class I

52 - Bone White 70% KYNAR® (2-Coat)

71 - Standard 70% KYNAR® (2-Coat)  
Standard Color per Chart- Specify \_\_\_\_\_

71 - Custom 70% KYNAR® (2-Coat) - Specify \_\_\_\_\_

71 - Custom 70% KYNAR® (3-Coat) - Specify \_\_\_\_\_

**DOOR OPENING SIZE**

36" x 84"

Custom Single \_\_\_\_\_  
Door Tag # \_\_\_\_\_

72" x 84"

Custom Pair \_\_\_\_\_  
Door Tag # \_\_\_\_\_

Maximum Leaf Size 48" x 96"

**GLASS STOP**

1" (25 mm) Square Glass Stops

**TOP RAIL - INCLUDES GLASS STOP**

4-5/16" HT101 (Standard)

2-7/8" HT201

6" WT201

**BOTTOM RAIL - INCLUDES GLASS STOP**

7-1/4" JT650 (Standard)

4-5/16" HT101

6" WT201

10" WT196

**MUNTINS - INCLUDES GLASS STOP**

3-5/8" (HT202)

5-1/16" (MT101)

6-3/4" (MT201)

8" (JT650)

10-3/4" (MT196)

**DOOR SWING                      QTY**

LHR Hinge Left Swing Out \_\_\_\_\_ ea.

RHR Hinge Right Swing Out \_\_\_\_\_ ea.

LH Hinge Left Swing In \_\_\_\_\_ ea.

RH Hinge Right Swing In \_\_\_\_\_ ea.

PAIR Swing In \_\_\_\_\_ ea.

PAIR Swing Out \_\_\_\_\_ ea.

**DOOR HINGING**

Top/Bottom and Intermediate Offset Pivots (OP500/DH010)

• Additional Pivot  DH010  
Add \_\_\_\_\_ per Door

1-1/2 Pair Butt Hinges (DH009)  
Add \_\_\_\_\_ per Door

Additional Butt Hinge  
Add \_\_\_\_\_ per Door

Continuous Geared Hinge (DH492)

By USALUM

By Customer

Prep and Supply

Prep Only (Selection Above)

No Prep

**HARDWARE FINISH                      DOOR FINISH**

• Clear    11, 12, 52, 71

• Bronze    22

Specify \_\_\_\_\_

**DOOR SWEEP**

Yes     No

Exposed Fasteners

Concealed Fasteners

**LOCKING OPTIONS**

MS Hookbolt With Two Cylinders - STD

Long Throw Deadlock With Cylinders

3-Point Locking @ Pair With Cylinders

Latch/Deadlock (DH189) With Cylinders

Thumbturn in Lieu of Cylinder

Latchlock (DH002)

Cylinder (Ext.)     Cylinder (Int.)

Thumbturn (Int.)

Lock Indicator

Cylinder Guard

Flushbolts (DH008)

Paddle Handle

• DH569 Lever Handle

Interior     Back to Back

• CRL DL2150 Lever Handle

Interior     Back to Back

Electric Strike

Prep and Supply     Prep Only

**PANIC DEVICES**

Jackson 1285 Concealed Vertical Rod Panic

Jackson 1295 Rim Panic Device

Jackson 2086 Concealed Vertical Rod Panic

Jackson 2095 Rim Panic Device

Jackson 1085 Concealed Vertical Rod Panic

Jackson 1095 Rim Panic Device

Adams-Rite 8400 Mortise Panic Device

Adams-Rite 8600 Concealed Vertical Rod Panic

Adams-Rite 8800 Rim Panic Device

with cylinder     cylinder by others (prep only)

Von Duprin® 33AE     Von Duprin® 35AE

Von Duprin® 3327AE     Von Duprin® 3527AE

Von Duprin® 3347AE     Von Duprin® 3547AE

• Outside Von Duprin Trim

360L     360T     388NL

with cylinder     cylinder by others (prep only)

Exit Only

By USALUM

By Customer

Prep and Supply

Prep Only (Selection Above)

**FOR OFFICE USE ONLY**

TAKEN BY: \_\_\_\_\_

PRICED BY: \_\_\_\_\_

EDITED BY: \_\_\_\_\_

**PUSH/PULL HARDWARE**

- Standard Push/Pull
- Offset Pulls
- None \_\_\_\_\_
- Custom     By USALUM     By Customer
- Prep and Supply     Prep Only

**NOTE:** Prep Only Requires Manufacturer's Name , Model, and Template

Manufacturer: \_\_\_\_\_

Model: \_\_\_\_\_

**DOOR CLOSER**

- O.H. Concealed (Offset-Prep Only)
- Standard Jackson Closer (Supply)
- 90°     105°    Hold Open     Yes     No
- CRL Surface Mount Closer (Supply)
- Drop Plate
- Door Stop/Holder Degree \_\_\_\_\_
- No Closer Required
- Custom     By USALUM     By Customer
- Prep and Supply     Prep Only

**NOTE:** Prep Only Requires Manufacturer's Name , Model, and Template

Manufacturer: \_\_\_\_\_

Model: \_\_\_\_\_

**FRAME SYSTEM**

Series IT451 2" x 4-1/2"     Open Back Subframe     1" x 4-1/2" (Thermal) Tubular Only

**FRAME TYPE**

- Up and Over (No Transom)
- 126" (3.2 m) High With Transom
- Frame Only
- Door Only (No Frame)
- Custom

**CLEARANCES/THRESHOLD**

Clearance from Bottom of Door to Finish Floor

- 11/16" Standard (Required for OP500 Pivot Set)
- Custom Clearance

Specify \_\_\_\_\_

- TT245 1/2" Threshold

**ADDITIONAL NOTES OR SKETCHES**

**FOR OFFICE USE ONLY**

TAKEN BY: \_\_\_\_\_

PRICED BY: \_\_\_\_\_

EDITED BY: \_\_\_\_\_

APPROVED BY \_\_\_\_\_

DATE \_\_\_\_\_