

CR LAURENCE CO., INC.

THERMAL PERFORMANCE TEST REPORT

SCOPE OF WORK

HP3252 GLAZED WALL SYSTEM

REPORT NUMBER

K0614.01-301-46

TEST DATE

09/24/19

ISSUE DATE

01/09/20

RECORD RETENTION END DATE

09/24/24


PAGES

24

DOCUMENT CONTROL NUMBER

RTTDS-R-AMER-Test-2822(a) (07/07/18)

©2017 INTERTEK



TEST REPORT FOR CR LAURENCE CO., INC.

Report No.: K0614.01-301-46

Date: 01/09/20

REPORT ISSUED TO

CR LAURENCE CO., INC.

2503 East Vernon Avenue

Los Angeles, California 90058

SECTION 1

SCOPE

SERIES/MODEL: HP3252

TYPE: Glazed Wall System

Intertek Building & Construction (Intertek B&C) was contracted by CR Laurence Co., Inc. to evaluate the thermal performance per NFRC 102-2017. The purpose of this testing was to evaluate the U-Factor performance. Results obtained are tested values and were secured by using the designated test method. Testing was conducted at Intertek B&C test facility in Fresno, California. This report does not constitute certification of this product nor an opinion or endorsement by this laboratory.

SECTION 2

SUMMARY OF TEST RESULTS

Standardized U-factor (Ust):

0.39 Btu/hr·ft²·F (CTS Method)

For INTERTEK B&C:

COMPLETED BY William Simon Smeds

TITLE Technician

SIGNATURE

DATE 01/09/20

WSS:ss

REVIEWED BY Kenny C. White

TITLE Laboratory Manager, IIRC

SIGNATURE

DATE 01/09/20

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample(s) tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT FOR CR LAURENCE CO., INC.

Report No.: K0614.01-301-46

Date: 01/09/20

SECTION 3

TEST SPECIMEN SUMMARY

SERIES/MODEL	HP3252
TYPE	Glazed Wall System
OVERALL SIZE	78-3/4" x 78-3/4" (2000 mm x 2000 mm) (Model Size)
NFRC STANDARD SIZE	78.7" x 78.7" (2000 mm wide x 2000 mm high)
TEST SAMPLE SUBMITTED BY	C.R. Laurence Co., Inc. - Vernon, California
TEST SAMPLE SUBMITTED FOR	Validation for Initial Certification (Production Line Unit) & Plant Qualification

SECTION 4

TEST METHOD

The specimens were evaluated in accordance with the following:

NFRC 102-2017, Procedure for Measuring the Steady-State Thermal Transmittance of Fenestration Systems

SECTION 5

MATERIAL SOURCE/INSTALLATION

The test specimen was provided by C.R. Laurence Co., Inc. - Vernon, California. Representative samples of the test specimen will be retained by Intertek B&C for a minimum of two and half years from the submittal date to the Inspection Agency and no more than five years from the test date.

Test Chamber Installation

The test sample was installed in a vertical orientation, the exterior of the specimen was exposed to the cold side.

SECTION 6

LIST OF OFFICIAL OBSERVERS

NAME	COMPANY
William Simon Smeds	Intertek B&C

TEST REPORT FOR CR LAURENCE CO., INC.

Report No.: K0614.01-301-46

Date: 01/09/20

SECTION 7

TEST SAMPLE DESCRIPTION

Frame

MATERIAL	AT (0.31"): Aluminum with Thermal Breaks - All Members		
SIZE	78-3/4" x 78-3/4" (Model Size)		
DAYLIGHT OPENING	35-3/8" x 73-5/8" (x2)	GLAZING METHOD	Exterior
EXTERIOR COLOR	Grey	EXTERIOR FINISH	Anodized
INTERIOR COLOR	Grey	INTERIOR FINISH	Anodized
CORNER JOINERY	Square Cut / Screws / Sealed		

Glazing Information

LAYER 1	1/4"	Solarban 72VT (e=0.018*, #2)	
GAP	0.57"	SS-D: Stainless Steel Spacer	100% Air*
LAYER 2	1/4"	Clear	
GAS FILL METHOD	N/A*		

**Stated per Client/Manufacturer*

N/A Non-Applicable

TEST REPORT FOR CR LAURENCE CO., INC.

Report No.: K0614.01-301-46

Date: 01/09/20

SECTION 7 (CONTINUED)

TEST SAMPLE DESCRIPTION (CONTINUED)

Weatherstripping

DESCRIPTION	QUANTITY	LOCATION
No weatherstripping.		

Hardware

DESCRIPTION	QUANTITY	LOCATION
No hardware.		

Drainage

DRAINAGE METHOD	SIZE	QUANTITY	LOCATION
No visible weeps.			

TEST REPORT FOR CR LAURENCE CO., INC.

Report No.: K0614.01-301-46

Date: 01/09/20

SECTION 8

THERMAL TRANSMITTANCE (U-FACTOR): MEASURED TEST DATA

Heat Flows

1. Total Measured Input into Metering Box (Qtotal)	1338.24 Btu/hr
2. Surround Panel Heat Flow (Qsp)	43.67 Btu/hr
3. Surround Panel Thickness	8.00 inches
4. Surround Panel Conductance	0.0237 Btu/hr·ft ² ·F
5. Metering Box Wall Heat Flow (Qmb)	36.10 Btu/hr
6. EMF vs Heat Flow Equation (equivalent information)	0.0211*EMF + 0.000
7. Flanking Loss Heat Flow (Qfl)	7.90 Btu/hr
8. Net Specimen Heat Loss (Qs)	1250.57 Btu/hr

Areas

1. Test Specimen Projected Area (As)	43.07 ft ²
2. Test Specimen Interior Total (3-D) Surface Area (Ah)	57.93 ft ²
3. Test Specimen Exterior Total (3-D) Surface Area (Ac)	47.15 ft ²
4. Metering Box Opening Area (Amb)	69.44 ft ²
5. Metering Box Baffle Area (Ab1)	60.56 ft ²
6. Surround Panel Interior Exposed Area (Asp)	26.37 ft ²

Test Conditions

1. Average Metering Room Air Temperature (th)	69.80 F
2. Average Cold Side Air Temperature (tc)	-0.38 F
3. Average Guard/Environmental Air Temperature	74.00 F
4. Metering Room Average Relative Humidity	12.66 %
5. Metering Room Maximum Relative Humidity	13.44 %
6. Metering Room Minimum Relative Humidity	11.93 %
7. Measured Cold Side Wind Velocity (Perpendicular Flow)	12.66 mph
8. Measured Warm Side Wind Velocity (Parallel Flow)	0.04 mph
9. Measured Static Pressure Difference Across Test Specimen	0.00" ± 0.04" H ₂ O

Average Surface Temperatures

1. Metering Room Surround Panel	68.92 F
2. Cold Side Surround Panel	-0.87 F

Results

1. Thermal Transmittance of Test Specimen (Us)	0.41 Btu/hr·ft ² ·F
2. Standardized Thermal Transmittance of Test Specimen (Ust)	0.39 Btu/hr·ft ² ·F

TEST REPORT FOR CR LAURENCE CO., INC.

Report No.: K0614.01-301-46

Date: 01/09/20

SECTION 9

THERMAL TRANSMITTANCE (U-FACTOR): CALCULATED TEST DATA

CTS Method Results

1. Warm Side Emittance of Glass (e1)	0.84
2. Cold Side Emittance of Glass	0.84
3. Warm Side Frame Emittance*	0.80
4. Cold Side Frame Emittance*	0.80
5. Warm Side Sash/Panel/Vent Emittance*	N/A
6. Cold Side Sash/Panel/Vent Emittance*	N/A
7. Warm Side Baffle Emittance (eb1)	0.92
8. Cold Side Baffle Emittance (eb2)	N/A
9. Equivalent Warm Side Surface Temperature (t1)	49.43 F
10. Equivalent Cold Side Surface Temperature (t2)	5.46 F
11. Warm Side Baffle Surface Temperature	69.64 F
12. Cold Side Baffle Surface Temperature	N/A F
13. Measured Warm Side Surface Conductance (hh)	1.43 Btu/hr·ft ² ·F
14. Measured Cold Side Surface Conductance (hc)	4.98 Btu/hr·ft ² ·F
15. Test Specimen Thermal Conductance (Cs)	0.66 Btu/hr·ft ² ·F
16. Convection Coefficient (Kc)	0.32 Btu/(hr·ft ² ·F ^{1.25})
17. Radiative Test Specimen Heat Flow (Qr1)	653.24 Btu/hr
18. Conductive Test Specimen Heat Flow (Qc1)	597.33 Btu/hr
19. Radiative Heat Flux of Test Specimen (qr1)	15.17 Btu/hr·ft ² ·F
20. Convective Heat Flux of Test Specimen (qc1)	13.87 Btu/hr·ft ² ·F
21. Standardized Warm Side Surface Conductance (hsth)	1.20 Btu/hr·ft ² ·F
22. Standardized Cold Side Surface Conductance (hstc)	5.28 Btu/hr·ft ² ·F
23. Standardized Thermal Transmittance (Ust)	0.39 Btu/hr·ft ² ·F

*Stated per NFRC 101

SECTION 10

TEST DURATION

1. The environmental systems were started at 13:52 hours, 09/23/19.
2. The test parameters were considered stable for two consecutive four hour test periods from 23:03 hours, 09/23/19 to 07:03 hours, 09/24/19.
3. The thermal performance test results were derived from 03:03 hours, 09/24/19 to 07:03 hours, 09/24/19.

TEST REPORT FOR CR LAURENCE CO., INC.

Report No.: K0614.01-301-46

Date: 01/09/20

SECTION 11

GLAZING DEFLECTION

	Left Glazing	Right Glazing
EDGE GAP WIDTH	0.57"	0.57"
ESTIMATED CENTER GAP WIDTH upon receipt of specimen in laboratory (after stabilization)	0.52"	0.48"
CENTER GAP WIDTH at laboratory ambient conditions on day of testing	0.52"	0.48"
CENTER GAP WIDTH at test conditions	0.43"	0.41"

Glass collapse determined using a digital glass and air space meter

The sample was inspected for the formation of frost or condensation, which may influence the surface temperature measurements. The sample showed no evidence of condensation/frost at the conclusion of the test.

“This test method does not include procedures to determine the heat flow due to either air movement through the specimen or solar radiation effects. As a consequence, the thermal transmittance results obtained do not reflect performances which are expected from field installations due to not accounting for solar radiation, air leakage effects, and the thermal bridge effects that have the potential to occur due to the specific design and construction of the fenestration system opening. The latter can only be determined by in-situ measurements. Therefore, it is important to recognize that the thermal transmittance results obtained from this test method are for ideal laboratory conditions and should only be used for fenestration product comparisons and as input to thermal performance analyses which also include solar, air leakage and thermal bridge effects.”

Required annual calibrations for the Intertek B&C, 'thermal test chamber' (ICN 004287) in Fresno, California were last conducted in October 2018 in accordance with Intertek B&C calibration procedure. A CTS Calibration verification was performed December 2018. A Metering Box Wall Transducer and Surround Panel Flanking Loss Characterization was performed March 2019.

The reported Standardized Thermal Transmittance (Ust) was determined using CTS Method, per Section 9.2(A) of NFRC 102.

TEST REPORT FOR CR LAURENCE CO., INC.

Report No.: K0614.01-301-46

Date: 01/09/20

SECTION 12**CTS CALIBRATION DATA**

1. CTS Test Date	11/03/17
2. CTS Size	43.06 ft ²
3. CTS Glass/Core Conductance	0.40 Btu/hr·ft ² ·F
4. Warm Side Air Temperature	69.81 F
5. Cold Side Air Temperature	-0.33 F
6. Warm Side Average Surface Temperature	55.03 F
7. Cold Side Average Surface Temperature	3.79 F
8. Convection Coefficient (Kc)	0.32 Btu/(hr·ft ² ·F ^{1.25})
9. Measured Cold Side Surface Conductance (hc)	4.98 Btu/hr·ft ² ·F
10. Measured Thermal Transmittance	0.31 Btu/hr·ft ² ·F

ANSI/NCSL Z540-2-1997 type B uncertainty for this test was 1.57%.

"Ratings included in this report are for submittal to an NFRC licensed IA for certification purposes and are not meant to be used for labeling purposes. Only those options identified on a valid Certificate of Authorization (CA) are to be used for labeling purposes."

The direction of heat transfer was from the interior (warm side) to the exterior (cold side) of the specimen. The ratings were rounded in accordance to NFRC 601, NFRC Unit and Measurement Policy. The data acquisition frequency is 5 minutes.


TEST REPORT FOR CR LAURENCE CO., INC.

Report No.: K0614.01-301-46

Date: 01/09/20

SECTION 13

SURROUND PANEL WIRING DIAGRAM




TEST REPORT FOR CR LAURENCE CO., INC.

Report No.: K0614.01-301-46

Date: 01/09/20

SECTION 14

BAFFLE WIRING DIAGRAM



TEST REPORT FOR CR LAURENCE CO., INC.

Report No.: K0614.01-301-46

Date: 01/09/20


SECTION 15

SUBMITTAL FORM AND DRAWINGS

The test specimen drawings which follow have been reviewed by Intertek B&C and are representative of the test specimen(s) reported herein. Test specimen construction was verified by Intertek B&C per the drawings included in this report. Any deviations are documented herein or on the drawings.

NFRC PRODUCT CERTIFICATION PROGRAM

Submittal Form for Test Samples



For use by Manufacturers, Lineal Suppliers and Fabricators

1. Information on Production of the Test Sample (complete ALL fields):

Manufacturer: C.R. Laurence Co., Inc. Date of sample manufacture: 7/13/2019
Plant Address where manufactured: 2100 E. 38h Street
City: Vernon State: CA Zip Code: 90058
Name of IA: Associated Laboratories Inc. Phone: (214) 565-1094 Fax: _____

2. Product Information (complete APPLICABLE fields):

Existing Product Line ID (CPD) No.: _____ Product/Operator Type (Table 4-3 of NFRC 100): Curtainwall
Series/Model: HP3252

3. Test sample is being submitted for (select ONE):

- a. Validation for Initial Certification (prototype only) no plant qualification
- b. Validation for Initial Certification or Recertification (production line unit) & plant qualification
- c. Plant Qualification Only (production line unit)
- d. Test Only Alternative (production line unit) & plant qualification



I, Chien Huang, as the designated agent for C.R. Laurence Co., Inc. do hereby attest that the foregoing information is true to the best of my information, knowledge, and belief. Further, if the unit is identified in Section 3 as a production line unit, I hereby authorize the NFRC-accredited testing laboratory to send a copy of the test report to the IA identified above for plant qualification purposes pursuant to the NFRC Product Certification Program.


Signature: [Signature] Date: 9/25/2019

For Laboratory Use Only


1. Laboratory: INTERTEK
2. Date Sample Received: 8/9/19 Test Report #: K0614.01-301-46
3. Date Sample Tested: 9/24/19 By: SIMON SMEDS
4. Modifications made: NONE

Bill Of Materials - 3252 HP Curtain Wall		
CW905 ✓	Vertical Mullion - 5" Tubular	Anodized Aluminum
PC927 ✓	Horizontal Mullion - 5" Open Back	Anodized Aluminum
PW901 ✓	F-Cap	Anodized Aluminum
TB927 ✓	Polyamide Pressure Bar	Polyamide
PC931 ✓	Glazing Adapter - Perimeter Bar	Anodized Aluminum
CW950 ✓	Insert Plate	Anodized Aluminum
	Pour and Debridge	Urethane/Polyurethane
NP930 ✓	Interior Glazing Gasket	EPDM
NP927 ✓	Exterior Glazing Gasket	EPDM
NP928 ✓	Pressure Bar Gasket	Vinyl
SS905	Reinforcement	Rolled Steel
	Glass	
	1/4" Solarban72VT - 1/2" Air - 1/4" Clear	
	Spacer	
	Stainless Steel	


	Report #:	K0614-301-46
	Date:	01/08/20
	Verified by:	



Wood blocks in outer perimeter glazing channel




Head and Sill




Vertical Members

NP928




CW905



TB927

NP927

0.31" Thermal breaks




Replace F-CRL-20944 (Left Jamb), 20960 (V. Mull), and 20958 (Right Jamb)





Report #: K0614-301-46
 Date: 01/08/20
 Verified by: *[Signature]*

UNIVERSITY ALUMINUM CORPORATION 3800 W. 100th Street, Suite 100 Minneapolis, MN 55425 612.835.4600 www.universium.com	ARCHITECT CUSTOMER	PROJECT INSULATION/THERMAL BREAK/RESISTANCE	DATE 11/9/18
U.S. ALUMINUM CO. INC.	ARCHITECT	PROJECT COMMENTS UNIFORMITY	SCALE FULL SIZE
DRAWN BY J. FREY		SHEET 1	



intertek Total Quality Assured.

Report #: K0614-301-46
 Date: 01/08/20
 Verified by: *[Signature]*



REV	DESCRIPTION	DATE	APP'D
B	4.175 WAS 4.188; .188 WAS .148; RECALC	11/11/07	GAH

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED UNLESS OTHERWISE SPECIFIED UNLESS OTHERWISE SPECIFIED UNLESS OTHERWISE SPECIFIED UNLESS OTHERWISE SPECIFIED UNLESS OTHERWISE SPECIFIED	DATE: 01/08/20 DRAWN BY: [Signature] CHECKED BY: [Signature] APPROVED BY: [Signature]	SCALE: 4 X SIZE PART: C/VR50	C. LAURENCE CO. 3800 E. Ventura Avenue, Los Angeles, CA 90008-1897 PH: (800) 421-9200 FAX: (310) 516-7001
---	--	---------------------------------	---

ALLOY & TEMPER: 6063-T6	SQ. IN.	IN ²
ESTIMATED AREA: 0.200	LB	IN
ESTIMATED WEIGHT / FT: 0.364	IN	IN
ESTIMATED PERMETER: 9.288	IN	IN
EXTRUSION: 4.176 IN	OUT. PERM. 2.28	IN
CLASS: SOLID	CIRCLE SIZE: 4.3	IN
SECTION PROPERTIES:	IN ⁴	IN ³
I _x : 0.488	I _y : 0.228	IN ³
I _x : 0.001	I _y : 0.001	IN ³

○ R.010
△ R.012
□ R.015
× R.020
/ R.025
◊ R.031
◆ R.040
◇ R.062
◻ R.094



Total Quality. Assured.

2524 East Jensen Avenue
Fresno, California 93706

Telephone: 559-233-8705
Facsimile: 717-764-4129
www.intertek.com/building

TEST REPORT FOR CR LAURENCE CO., INC.

Report No.: K0614.01-301-46

Date: 01/09/20

SECTION 16

REVISION LOG

REVISION #	DATE	PAGES	REVISION
.01 R0	01/09/20	N/A	Original Report Issue