

**NFRC 102-2010 THERMAL PERFORMANCE  
TEST REPORT**

**Rendered to:**

**CR LAURENCE CO., INC.**

**SERIES/MODEL: BT525 - Window Wall**

**TYPE: Glazed Wall Systems (Site-built)**

<b>Summary of Results</b>	
<b>Standardized Thermal Transmittance (U-Factor)</b>	0.38
<b>Unit Size:</b>	79-3/8" x 79-1/4" (2016 mm x 2013 mm) (Non-Standard Size)
<b>Layer 1:</b> 1/4"	Clear
<b>Gap:</b> 0.52"	A1-D: Aluminum Spacer   100% Air*
<b>Layer 2:</b> 1/4"	PPG Solarban 70XL (e=0.018*, #3)

Reference must be made to Report No. C9659.01-301-46, dated 01/09/14 for complete test specimen description and data.

**NFRC 102-2010 THERMAL PERFORMANCE TEST REPORT**

Rendered to:

CR LAURENCE CO., INC.  
2100 East 38th Street  
Vernon, California 90058

Report Number: C9659.01-301-46  
Test Date: 12/29/13  
Report Date: 01/09/14

**Test Sample Identification:**

**Series/Model:** BT525 - Window Wall

**Type:** Glazed Wall Systems (Site-built)

**Overall Size:** 79-3/8" x 79-1/4" (2016 mm x 2013 mm) (Non-Standard Size)

**NFRC Standard Size:** 78.7" x 78.7" (2000 mm wide x 2000 mm high)

**Test Sample Submitted by:** Client

**Test Sample Submitted for:** Validation for Initial Certification (Prototype only) no Plant Qualification

**Test Procedure:** U-factor tests were performed in a Guarded Hot Box in accordance with NFRC 102-2010, *Procedure for Measuring the Steady-State Thermal Transmittance of Fenestration Systems*.

**Test Results Summary:**

Standardized U-factor ( $U_{st}$ ): 0.38 Btu/hr·ft<sup>2</sup>·F (CTS Method)

**Test Sample Description:**

**Frame:**

<b>Material:</b>	AT (0.21"): Aluminum with Thermal Breaks - All Members		
<b>Size:</b>	79-3/8" x 79-1/4" (Non-Standard Size)		
<b>Daylight Opening:</b>	36" x 74" (x2)	<b>Glazing Method:</b>	Exterior
<b>Exterior Color:</b>	Grey	<b>Exterior Finish:</b>	Anodized
<b>Interior Color:</b>	Grey	<b>Interior Finish:</b>	Anodized
<b>Corner Joinery:</b>	Square Cut / Screws / Sealed		

**Glazing Information:**

<b>Layer 1:</b>	1/4"	Clear	
<b>Gap:</b>	0.52"	A1-D: Aluminum Spacer	100% Air*
<b>Layer 2:</b>	1/4"	PPG Solarban 70XL (e=0.018*, #3)	
<b>Gas Fill Method:</b>	N/A*		

*\*Stated per Client/Manufacturer*

*N/A Non-Applicable*

**Test Sample Description:** (Continued)

**Weatherstripping:**

Description	Quantity	Location
No weatherstripping		

**Hardware:**

Description	Quantity	Location
No hardware		

**Drainage:**

Drainage Method	Size	Quantity	Location
No visible weeps			

## Thermal Transmittance (U-factor)

### Measured Test Data

#### Heat Flows

1. Total Measured Input into Metering Box ( $Q_{total}$ )	1274.85 Btu/hr
2. Surround Panel Heat Flow ( $Q_{sp}$ )	52.27 Btu/hr
3. Surround Panel Thickness	6.00 inches
4. Surround Panel Conductance	0.0296 Btu/hr·ft <sup>2</sup> ·F
5. Metering Box Wall Heat Flow ( $Q_{mb}$ )	-4.97 Btu/hr
6. EMF vs Heat Flow Equation (equivalent information)	0.0218*EMF + 0.000
7. Flanking Loss Heat Flow ( $Q_{fl}$ )	20.53 Btu/hr
8. Net Specimen Heat Loss ( $Q_s$ )	1207.02 Btu/hr

#### Areas

1. Test Specimen Projected Area ( $A_s$ )	43.68 ft <sup>2</sup>
2. Test Specimen Interior Total (3-D) Surface Area ( $A_h$ )	53.16 ft <sup>2</sup>
3. Test Specimen Exterior Total (3-D) Surface Area ( $A_c$ )	44.14 ft <sup>2</sup>
4. Metering Box Opening Area ( $A_{mb}$ )	69.44 ft <sup>2</sup>
5. Metering Box Baffle Area ( $A_{bi}$ )	60.56 ft <sup>2</sup>
6. Surround Panel Interior Exposed Area ( $A_{sp}$ )	25.76 ft <sup>2</sup>

#### Test Conditions

1. Average Metering Room Air Temperature ( $t_h$ )	69.44 F
2. Average Cold Side Air Temperature ( $t_c$ )	-0.45 F
3. Average Guard/Environmental Air Temperature	74.01 F
4. Metering Room Average Relative Humidity	14.23 %
5. Metering Room Maximum Relative Humidity	14.27 %
6. Metering Room Minimum Relative Humidity	14.17 %
7. Measured Cold Side Wind Velocity (Perpendicular Flow)	12.66 mph
8. Measured Warm Side Wind Velocity (Parallel Flow)	0.04 mph
9. Measured Static Pressure Difference Across Test Specimen	0.00" ± 0.04"H <sub>2</sub> O

#### Average Surface Temperatures

1. Metering Room Surround Panel	68.50 F
2. Cold Side Surround Panel	0.03 F

#### Results

1. Thermal Transmittance of Test Specimen ( $U_s$ )	0.40 Btu/hr·ft <sup>2</sup> ·F
2. Standardized Thermal Transmittance of Test Specimen ( $U_{st}$ )	0.38 Btu/hr·ft <sup>2</sup> ·F

## Thermal Transmittance (U-factor)

### Calculated Test Data

#### CTS Method

1. Warm Side Emittance of Glass ( $e_i$ )	0.84
2. Cold Side Emittance of Glass	0.84
3. Warm Side Frame Emittance*	0.80
4. Cold Side Frame Emittance*	0.80
5. Warm Side Sash/Panel/Vent Emittance*	N/A
6. Cold Side Sash/Panel/Vent Emittance*	N/A
7. Warm Side Baffle Emittance ( $e_{b1}$ )	0.92
8. Cold Side Baffle Emittance ( $e_{b2}$ )	N/A
9. Equivalent Warm Side Surface Temperature	49.99 F
10. Equivalent Cold Side Surface Temperature	5.26 F
11. Warm Side Baffle Surface Temperature	69.20 F
12. Cold Side Baffle Surface Temperature	N/A F
13. Measured Warm Side Surface Conductance ( $h_h$ )	1.42 Btu/hr·ft <sup>2</sup> ·F
14. Measured Cold Side Surface Conductance ( $h_c$ )	4.84 Btu/hr·ft <sup>2</sup> ·F
15. Test Specimen Thermal Conductance ( $C_s$ )	0.62 Btu/hr·ft <sup>2</sup> ·F
16. Convection Coefficient ( $K_c$ )	0.32 Btu/(hr·ft <sup>2</sup> ·F <sup>1.25</sup> )
17. Radiative Test Specimen Heat Flow ( $Q_{r1}$ )	629.98 Btu/hr
18. Conductive Test Specimen Heat Flow ( $Q_{c1}$ )	577.04 Btu/hr
19. Radiative Heat Flux of Test Specimen ( $q_{r1}$ )	14.42 Btu/hr·ft <sup>2</sup> ·F
20. Convective Heat Flux of Test Specimen ( $q_{c1}$ )	13.21 Btu/hr·ft <sup>2</sup> ·F
21. Standardized Warm Side Surface Conductance ( $h_{sth}$ )	1.20 Btu/hr·ft <sup>2</sup> ·F
22. Standardized Cold Side Surface Conductance ( $h_{stc}$ )	5.28 Btu/hr·ft <sup>2</sup> ·F
23. Standardized Thermal Transmittance ( $U_{st}$ )	0.38 Btu/hr·ft <sup>2</sup> ·F

#### Test Duration

1. The environmental systems were started at 09:18 hours, 12/28/13.
2. The test parameters were considered stable for two consecutive four hour test periods from 06:12 hours, 12/29/13 to 14:12 hours, 12/29/13.
3. The thermal performance test results were derived from 10:12 hours, 12/29/13 to 14:12 hours, 12/29/13.

The reported Standardized Thermal Transmittance ( $U_{st}$ ) was determined using CTS Method, per Section 8.2(A) of NFRC 102.

*\*Stated per NFRC 101*

**Glazing Deflection:**

	<b>Left Glazing</b>	<b>Right Glazing</b>
Edge Gap Width	0.52"	0.52"
Estimated center gap width upon receipt of specimen in laboratory (after stabilization)	0.50"	0.55"
Center gap width at laboratory ambient conditions on day of testing	0.50"	0.55"
Center gap width at test conditions	0.41"	0.46"

*Glass collapse determined using a digital glass and air space meter*

The sample was inspected for the formation of frost or condensation, which may influence the surface temperature measurements. The sample showed no evidence of condensation/frost at the conclusion of the test.

“This test method does not include procedures to determine the heat flow due to either air movement through the specimen or solar radiation effects. As a consequence, the thermal transmittance results obtained do not reflect performances which are expected from field installations due to not accounting for solar radiation, air leakage effects, and the thermal bridge effects that have the potential to occur due to the specific design and construction of the fenestration system opening. The latter can only be determined by in-situ measurements. Therefore, it is important to recognize that the thermal transmittance results obtained from this test method are for ideal laboratory conditions and should only be used for fenestration product comparisons and as input to thermal performance analyses which also include solar, air leakage and thermal bridge effects.”

The test sample was installed in a vertical orientation, the exterior of the specimen was exposed to the cold side. The direction of heat transfer was from the interior (warm side) to the exterior (cold side) of the specimen. The ratings were rounded in accordance to NFRC 601, NFRC Unit and Measurement Policy. The data acquisition frequency is 5 minutes.

ANSI/NCSL Z540-2-1997 type B uncertainty for this test was 1.56%.

Required annual calibrations for the Architectural Testing Inc. 'thermal test chamber' (ICN 004287) in Fresno, California were last conducted in May 2013 in accordance with Architectural Testing Inc. calibration procedure. A CTS Calibration verification was performed October 2013. A Metering Box Wall Transducer and Surround Panel Flanking Loss Characterization was performed May 2013.

"Ratings included in this report are for submittal to an NFRC licensed IA for certification purposes and are not meant to be used for labeling purposes. Only those values identified on a valid Certification Authorization Report (CAR) are to be used for labeling purposes."

Architectural Testing, Inc. will service this report for the entire test record retention period. Test records that are retained such as detailed drawings, datasheets, representative samples of test specimens, or other pertinent project documentation will be retained by Architectural Testing, Inc. for the entire test record retention period. The test record retention end date for this report is January 09, 2018.

This report does not constitute certification of this product nor an opinion or endorsement by this laboratory. It is the exclusive property of the client so named herein and relates only to the specimen tested. This report may not be reproduced, except in full, without the written approval of Architectural Testing, Inc.

For ARCHITECTURAL TESTING, INC.

Tested By:



Digitally Signed by: William Smeds

William Simon Smeds  
Technician

Reviewed By:




Digitally Signed by: Kenny C. White

Kenny C. White  
Laboratory Manager  
Individual-In-Responsible-Charge

WSS:ss  
C9659.01-301-46

Attachments (pages): This report is complete only when all attachments listed are included.

- Appendix-A: CTS Calibration Data (1)
- Appendix-B: Surround Panel Wiring Diagram (1)
- Appendix-C: Baffle Wiring Diagram (1)
- Appendix-D: Submittal Form and Drawings (8)

	Architectural Testing, Inc. is accredited by the International Accreditation Service (IAS) under the specific test methods listed under lab code TL-144, in accordance with the recognized International Standard ISO/IEC 17025:2005. The laboratory's accreditation or test report in no way constitutes or implies product certification, approval, or endorsement by IAS.
---	--




### Revision Log


<u>Rev. #</u>	<u>Date</u>	<u>Page(s)</u>	<u>Revision(s)</u>
0	01/09/14	All	Original Report Issue. Work requested by Mr. Brian Rutherford of CR Laurence Co., Inc.

**Appendix A: CTS Calibration Data**

1. CTS Test Date	07/06/13
2. CTS Size	43.06 ft <sup>2</sup>
3. CTS Glass/Core Conductance	0.40 Btu/hr·ft <sup>2</sup> ·F
4. Warm Side Air Temperature	69.80 F
5. Cold Side Air Temperature	-0.15 F
6. Warm Side Average Surface Temperature	55.01 F
7. Cold Side Average Surface Temperature	4.06 F
8. Convection Coefficient (K <sub>c</sub> )	0.32 Btu/(hr·ft <sup>2</sup> ·F <sup>1.25</sup> )
9. Measured Cold Side Surface Conductance (h <sub>c</sub> )	4.84 Btu/hr·ft <sup>2</sup> ·F
10. Measured Thermal Transmittance	0.31 Btu/hr·ft <sup>2</sup> ·F

### Appendix B: Surround Panel Wiring Diagram




**Appendix C: Baffle Wiring Diagram**

**Appendix D: Submittal Form and Drawings**

**NFRC PRODUCT CERTIFICATION PROGRAM**

**Submission Form for Test Samples**

For use by manufacturers, lineal suppliers and fabricators



National Fenestration  
Rating Council®

1. Information on Production of the Test Sample (complete ALL fields):

Manufacturer: C.R. LAURENCE CO., INC. Date of sample manufacture: DEC. 11, 2013  
Plant Address where manufactured: 2100 E. 98TH ST.  
City: LOS ANGELES State: CA Zip Code: 90058  
Name of IA: ALI Phone: 214-565-0593 Fax: 214-565-1094

2. Product Information (complete ALL fields):

Product Line ID (CPD) No.: \_\_\_\_\_ Product/Operator Type (Table 4-3 of NFRC 100): CW/WW/GLOPED  
Series/Model: BT525 - WINDOW WALL

3. Test sample is being submitted for (select ONE):

- a.  Validation for Initial Certification (prototype only) no plant qualification
- b.  Validation for Initial Certification (production line unit) & plant qualification
- c.  Validation for Recertification (production line unit) & plant qualification
- d.  Plant Qualification Only (production line unit)

I, RONALD WOOTEN, as the designated agent for C.R. LAURENCE CO., INC.  
do hereby attest that the foregoing information is true to the best of my information, knowledge, and belief.  
Further, if the unit is identified in Section 3 as a production line unit, I hereby authorize the NFRC-accredited  
testing laboratory to send a copy of the test report to the IA identified above for plant qualification purposes  
pursuant to the NFRC Product Certification Program.

Signature: [Signature] Date: 1-06-2014

FOR LABORATORY USE ONLY

1. Laboratory: Architectural Testing, Inc.  
2. Date Sample Received: 12/19/13 File number ID: 19659.01-301-46  
3. Date Sample Tested: 12/29/13 By: William Smedley  
4. Modifications made: NONE

5. Reason for non-testing of sample unit: N/A

[Note: If the sample submitted can not be tested due to damage prior to testing, a new sample and new form shall be submitted to the testing laboratory. Both forms shall be submitted to the IA when the testing is completed.]

ID	Qty	Description	Material	Finish	Width	Height
	1	BT525 Window Wall			79.000	X 79.000
	2	1" Insulated Glass			77.931	X 20.378
		<b>HORIZONTALS</b>				
Part	Qty	Description			Length	
<del>BT568</del> BT566	2	HEAD/SILL 5-1/4"	6063-T5 Aluminum w/ Polyurethane Thermal Break - Fully Debrided	Anodized	79.000	
	2	INSERT - HEAD/SILL 5-1/4"	6063-T5 Aluminum	Anodized	79.000	
BT768	2	HEAD/SILL 6"	6063-T5 Aluminum w/ Polyurethane Thermal Break - Fully Debrided	Anodized	79.000	
BG766	2	INSERT - HEAD/SILL 6"	6063-T5 Aluminum	Anodized	79.000	
BG334	1	SETTING CHAIR FOR SILL	6063-T5 Aluminum	Anodized	4" each, 2 per lite	
		<b>VERTICALS</b>				
BG550	1	VERT. MULLION 5-1/4"	6063-T5 Aluminum	Anodized	74.500	
BG650	1	VERT. MULLION 6"	6063-T5 Aluminum	Anodized	74.500	
		<b>ACCESSORIES</b>				
<del>NP225</del> SB334	4	GASKET	EPDM, 70 Shore A, Black		36.125	
	4	SETTING BLOCK	EPDM, 90 Shore A, Black		4.000	
SP455	4	SPACER	EPDM, 70 Shore A, Black		74.500	


Architectural Testing, Inc.  
Test sample compliance with these details  
exceptions and notes

JAN 08 2014



09659

Date

Report #                       
Tech



0.21 Thermal Break




**A** Architectural Testing, Inc.  
 Test sample complies with these details  
 conditions are noted

C 9 6 5 9

JAN 06 2014

Report # Tech LS5 Date



4" each, 2 per lite